



Tuff Lite Solid Stainless Steel Swing Doors

Doors Shown Below Feature Optional
ABS Impact Panels and a Stainless Steel Frame

Technical Specifications

- 16 gauge thick (.0598 inches).
- 2½ pounds of 304 brushed stainless steel per square foot.
- 3/16" thick acrylic window with gasket comes standard in each door panel.
- Low-maintenance stainless steel auto-closing hinges included.
- Can be mounted with hinges on either left or right door jamb.
- Made in the USA.
- Limited 1-year warranty on parts.
- Doors are prefabricated with standard widths, but custom heights are available up to 84" high.

Features:

- Door panels swing 180°.
- Available in single panel and double panel configurations.
- 100% comprised of 304 brushed stainless steel.
- Heavy-duty auto-closing hinges allow doors to open with less than a pound of pressure.
- Stain and scratch resistant.
- Easy to sanitize. No coating to absorb microorganisms.
- Modern, elegant, timeless style.
- ABS Impact plates are available for extra durability.
- Easy to clean and sanitize using stainless steel cleaner and a microfiber cloth.

Single Panel Configuration



Actual Panel Width	Window Size	Opening Width	Opening Height
29¼"	9-3/8"X16-3/8"	30" to 31"	78" to 84"
35¼"	12-3/8"X17-3/8"	36"	78" to 84"

Double Panel Configuration



Window Size	Opening Width	Opening Height
(2) 8-3/8"X12-3/8"	36"	78" to 84"
(2) 8-3/8"X12-3/8"	42"	78" to 84"
(2) 8-3/8"X12-3/8"	48"	78" to 84"
(2) 9-3/8"X16-3/8"	60"	78" to 84"
(2) 12-3/8"X17-3/8"	72"	78" to 84"

Toll Free:

855-883-3284 (855) TUFFBUILT

Doors Manufactured by World Manufacturing, Inc.

tuffbultdoors.com

TUFFBUILTDOORS.COM ©